

FEATURES

- 39-1/2" x 37-3/4" Shower Walls for new and existing construction.
- Thick 1/4" 100% solid surface material bonded to an 1-1/4" thick aluminum honeycomb polyurethane filled backer for superior strength. Fire retardant wood backer. Solid surface material is easy to clean and will not support bacteria growth.
- 3-piece wall design glues directly to studs with supplied adhesive. Back wall can be alternately installed with aluminum hanging rail provided.
- Aluminum channel joints for easy installation and uniform structure.
- Four wall shelves included for convenient storage.
- Wall Kit includes 8" long chrome shower arm, 15" slotted hanging rail.
- 10 Year Limited Residential Warranty / 3 Year Commercial Warranty

COLORS

- 3 Transitions colors with a 16" x 16" square tile pattern.
- 2 Classic colors with plain pattern

OPTIONS

- Dome Top slides in place and sits on top of the shower walls forming a complete 8' shower enclosure. The dome contains (1) waterproof UL approved 12 volt LED light (40 year life).
- Shower base with concealed drain. Trench drain (shown) and collapsible threshold (see separate specification sheet) models available.
- Safety grab bar sets, personal hand shower and fold-up shower seat.




Shown with FG3938 Shower Base, T3981 Dome Top and GB1529PS Grab Bar set, GBHS18PS Hand Shower


	SIZE	MODEL NO.	DESCRIPTION	Width	Depth	Height
COMPLETE SHOWER KITS						
Shower Kits with Trench Drain Base						
☐	39" x 38"	DKWFG3988	Walls & Base Kit	39½"	37¾"	83"
☐	39" x 38"	DKWFGT3988	Walls, Base, Dome Kit	39½"	37¾"	95¾"
SHOWER WALLS (only) KIT						
☐	39" x 38"	DKW3988	Wall Kit	39½"	37¾"	80"
	39" x 80"	DB398A	Back Wall (1 pc.)	39½"		80"
	38" x 80"	DE388A	End Wall Set (2 pcs.)		37¾"	80"
INDIVIDUAL COMPONENTS						
☐	39" x 38"	T3981	Dome Top	39½"	37¾"	12¾"
SHOWER BASE						
☐	39" x 38"	FG3938	Trench Drain	39½"	37¾"	3"

To Be Specified: Pattern/Color (see below)


16" Square Tile Pattern / Colors




	Shower Walls	Shower Base
☐	91 White Carrara	11 Storm
☐	94 Sand Mountain	14 Sand
☐	96 Almond Sky	05 Almond



Plain / Colors



	Shower Walls	Shower Base
☐	01 White	01 White
☐	86 Sea Shore	86 Sea Shore




INSTALLATION NOTES

This product is to be installed according to the installation guide.


Drain cutout in subfloor to be 4-1/2" diameter and located per the rough-in Illustration 1. Dry fit the shower base to ensure a proper fit and correct alignment of the shower drain and the hole in the floor.

Unit can be installed with aluminum hanging rail provided. Alternate adhesive method of installation can be used without the use of the hanging rail (see full instructions for details). Position of hanging rail mounting is also critical. See Illustration 2 for horizontal positioning of hanging rail. The top of the hanging rail to be positioned at 76" above finished floor when using a 3" high Transolid® shower base. When you do not use a Transolid® shower base the upper hanging rail should be installed 73" above the finished threshold.

Strong 2-layer construction



1 1/4" thick
Aluminum
Honeycomb
Backer _____
provides
strength
and structure.




1/4" thick
solid surface
material for
beauty and
smooth bacteria
free surface



Pre-drilled holes with stainless ferules allow for precise placement of grab bars



Concealed drain with color-matched lift-off drain cover, 2 1/4" mosaic tile pattern.



Trench drain allows for roll-in entry, but doesn't allow water to flow out of base.

Illustration 1





Illustration 2



	MODEL NO.	DESCRIPTION
A	DB398A	Back Wall (1 panel)
B	DE388AL	Left End Wall (1 panel)
C	DE388AR	Right End Wall (1 panel)
D	FG3938	Trench Drain Shower Base - center drain
E	T3981	Dome Top with (1) LED Light

Compliance Certifications - Meets or Exceeds the Following Specifications

- IGC 154-2012
- ASME A112.18.1 / CSA B125.125.1-11
- cUPC®



Showers will comply with the Americans with Disabilities Act when installed per requirements of the 2010 ADA Standards for Accessible Design, Section 608 Shower Compartments, of the Act.

OPTIONS: ACCESSORIES

Available for on-site installation. Must be ordered separately.
See Accessories Specification for further information.

SHOWER SEAT & GRAB BAR SETS		
	MODEL	DESCRIPTION
☐	H2513	Rectangular Fold-up Seat
☐	GB1529PS	1¼" Grab Bar Set: (1) 29" , (1) 15 " Stainless
☐	GB2929PS	1¼" Grab Bar Set: (3) 29" Pol. Stainless
☐	GBHS18PS	Hand Shower with 18" ADA Bar