

Features

- Heavy Duty SMC Sheet Molding Compound Material
- Trimslate shower bases with our unique adjustable depth threshold.
- Maximum depth can be adjusted by up to 2-1/2" without any trimming of the base.
- Trimslate bases can also be customized in the field to fit your space. Trim up to 4" in width from either side opposite drain or up to 2" in depth away from drain.
- For bases 60" in length or less, a 60" add on trimmable threshold is included.
- For longer bases, an 80" long add on trimmable threshold is supplied.
- The threshold has a 4" wide flat surface to accommodate shower doors.
- Modern stainless steel drain cover conceals a conventional 2" shower drain (not supplied). Color-matched SMC cover for SMFZST5140C, SMFZST6040C, SMFZST6340C, and SMFZST7940C.
- The slate floor has a lightly textured and slip-resistant surface that makes it safe, yet remains easy to clean.
- 1" high aluminum tiling flange included.
- Weight capacity of 2204.6 pounds (1000 kg).
- 10 Year Limited Residential / 3 Year Commercial Warranty



Stock Sized Specified Models

	Model No.	Length A	Min Width B	Max Width B	Height	Ship Wt. (lbs)
☐	SMFZST4836C	47.2"	36.5"	39"	2.75"	59.52
☐	SMFZST5140C	51.2"	40.5"	43"	2.75"	67.46
☐	SMFZST6032C	59.1"	32.5"	35"	2.75"	62.83
☐	SMFZST6036C	59.1"	36.5"	39"	2.75"	67.02
☐	SMFZST6040C	59.1"	40.5"	43"	2.75"	72.75
☐	SMFZST6042C	59.1"	42.5"	45"	2.75"	73.19
☐	SMFZST6048C	59.1"	48.5"	51"	2.75"	82.67
☐	SMFZST6332C	63"	32.5"	35"	2.75"	73.85
☐	SMFZST6336C	63"	36.5"	39"	2.75"	76.06
☐	SMFZST6340C	63"	40.5"	43"	2.75"	83.78
☐	SMFZST6642C	64.9"	42.5"	45"	2.75"	89.51
☐	SMFZST6648C	64.9"	48.5"	51"	2.75"	95.90
☐	SMFZST6736C	67"	36.5"	39"	2.75"	78.26
☐	SMFZST7236C	70.9"	36.5"	39"	2.75"	81.57
☐	SMFZST7242C	70.9"	42.5"	45"	2.75"	94.14
☐	SMFZST7248C	70.9"	48.5"	51"	2.75"	102.52
☐	SMFZST7940C	78.7"	40.5"	43"	2.75"	101.41

To Be Specified: Color

☐ 31 White		
☐ 32 Cameo	White 31	Dk Grey 40
☐ 40 Dark Grey		
☐ 09 Black	Cameo 32	Black 09

Meets or Exceeds the Following Specification

• ASME A112.18.1 / CSA B125.125.1-11

• cUPC® • IAPMO 

