

FEATURES

- An attractive, frameless smooth sliding Bypass shower door that features a special Nano Protected surface treatment that keeps glass looking clean.
- New TruMotion technology features premium engineered rolling mechanism system for easy gliding and quiet sliding door.
- Optional side wall profiles give up to 1" out-of-plumb adjustment on each side or 2" total.
- Walk-in opening: 26-5/8" to 28-1/4" for 60" width door.
- Clearance height: 75-7/8" for 80" height door.
- Tempered glass is ANSI Z97.1. certified.
- Glass thickness: 11/32" (8.5mm) available in Golden Sparkling and Silver Sparkling.
- Sparkling Glass has the colored film between two panels of 4mm clear glass.
- Exposed rollers with soft-close features and wall bracket. Frame is made from 304 stainless steel with top track having an internal aluminum support.
- Hardware finishes: Polished Chrome, Brushed Stainless, Champagne Bronze, and Matte Black.
- Shower base threshold minimum requirement is 3-3/8" wide.
- Doors come with a pair of 19-5/8" (500mm) Royston bypass handles.
- Easy to install.
- **IMPORTANT!** All measurements should be taken only **AFTER** walls are finished (tile, back walls, etc.); Professional installation recommended.
- Limited Lifetime Warranty for residential and 1 year for commercial.



Specify Model

	Size	Model	Glass	Width	Height	Weight (lbs)
☐	60X80	SMOBPT608009GP-	Golden (8.5 mm)	60"	80"	168
☐	60X80	SMOBPT608009SP-	Silver (8.5 mm)	60"	80"	168


To Be Specified : Hardware Color

☐	PC Chrome
☐	BS Brushed Stainless
☐	CB Champagne Bronze
☐	MB Matte Black



To Be Specified : Glass

☐	GP Golden Sparkling
☐	SP Silver Sparkling



***Royston handles are included**

