

FEATURES

- An attractive, frameless sliding Bypass shower door that features a special Nano Protected surface treatment that keeps glass looking clean.
- New TruMotion technology features premium engineered rolling mechanism system for easy gliding and quiet sliding door.
- Optional side wall profiles give up to 1" out-of-plumb adjustment on each side or 2" total.
- Walk-in opening: 20-5/8" to 22-1/4" for 48" width door and 26-5/8" to 28-1/4" for 60" width door.
- Clearance height: 57-7/8" for 62" height door and 75-7/8" for 80" height door.
- Tempered glass is ANSI Z97.1. certified.
- Glass thickness: 5/16" (8mm) available in Clear.
- Exposed rollers with soft-close features and wall bracket. Frame is made from 304 stainless steel with top track having an internal aluminum support.
- Hardware finishes: Polished Chrome, Brushed Stainless, Champagne Bronze, and Matte Black.
- Shower base threshold minimum requirement is 3-3/8" wide.
- Doors come with a pair of 19-5/8" (500mm) Riley bypass handles.
- Easy to install.
- **IMPORTANT!** All measurements should be taken only **AFTER** walls are finished (tile, back walls, etc.); Professional installation recommended.
- Limited Lifetime Warranty for residential and 1 year for commercial.



Specify Model

	Size	Model	Glass	Width	Height	Weight (lbs)
	48X80	OBPT488008C-	Clear (8 mm)	48"	80"	85
	60X62	OBPT606208C-	Clear (8 mm)	60"	62"	95
	60X80	OBPT608008C-	Clear (8 mm)	60"	80"	120

To Be Specified : Hardware Color

	PC Chrome
	BS Brushed Stainless
	CB Champagne Bronze
	MB Matte Black



To Be Specified : Glass

 C Clear



***Riley handles
are included**

