

Features

- Low profile single, double or peninsula shower base with natural stone effect.
- Ultra low 1" threshold front curb for easy access and finishes flush with most finished floors.
- Heavy duty Sheet Molding Compound material.
- Installation for new and existing construction.
- 1" high aluminum tiling flange included.
- Bases can be trimmed in the field to fit your space.
- Select from single, double or peninsula threshold.
- Slip resistant; lightly textured slate floor for a safe environment yet maintains an easy to clean surface.
- Color-matched SMC drain cover for end drain models. Drain not included.
- Optional threshold can be added to form a conventional base. Design is similar to other Trimslate bases and will accommodate the current add-on threshold.
- Weight capacity of 661.4 lbs (300 kg).
- 10 Year Limited Residential / 3 Year Commercial Warranty




Specified Models


	Model No.	Length A	Width B	Ctr C	Ctr D	Height	Ship Wt. (lbs)
☐	FZSP6032	59.1"	31.5"	29.55"	15.75"	1"	50.71
☐	FZSP6036	59.1"	35.5"	29.55"	17.75"	1"	55.12

To Be Specified: Color

☐	33 Beach
☐	39 Ashy Grey
☐	60 Calcite
☐	61 Sterling Black



Beach **33**



Ashy Grey **39**



Calcite **60**




Sterling Black **61**

CUSTOMIZABLE BASE

Note: Bases can be built to accommodate unique sizes. Notches can also be cut from the bases to allow for columns in a corner.

Base can be built to custom sizes within certain limitations. Can be trimmed up to 4" in width away from side opposite drain or up to 2" from depth on end drain models. Base is designed to be used as a single, double or triple threshold in stock sizes.





Codes/Standards

The specified model meets or exceeds the following:


ASTM E662

CSA B45.5/IAPMO Z124

Notes: Install this product according to the installation instructions.





Tiling flange



Modern Slip
Resistance
with a stone look
texture. Easy to
clean as well as
slip resistant.



FZSP6032



FZSP6036

