

Features

- Heavy Duty SMC Sheet Molding Compound Material
- Trimslate shower bases with our unique adjustable depth threshold.
- Maximum depth and width can be adjusted by up to 2-1/2" without any trimming of the base.
- Trimslate bases can also be customized in the field to fit your space. Trim up to 4" in width from either side or up to 2" in depth away from drain.
- Each base is supplied with two 80" long add on trimmable thresholds with a 45-degree mitered edge.
- The threshold has a 4" wide flat surface to accommodate shower doors.
- Modern stainless steel drain cover conceals a conventional 2" shower drain (not supplied). Color-matched SMC cover for FZSDT5140C, FZSDT6040C, FZSDT6340C, and FZSDT7940C.
- The slate floor has a lightly textured and slip-resistant surface that makes it safe, yet remains easy to clean.
- 1" high aluminum tiling flange included
- Weight capacity of 2204.6 pounds (1000 kg).
- 10 Year Limited Residential / 3 Year Commercial Warranty



Stock Sized Specified Models

	Model No.	Min Length A	Max Length A	Min Length B	Max Length B	Height	Ship Wt. (lbs)
☐	FZSDT4836C	48.2"	50.7"	36.5"	39"	2.75"	94.80
☐	FZSDT5140C	52.2"	54.7"	40.5"	43"	2.75"	102.74
☐	FZSDT6032C	60.1"	62.6"	32.5"	35"	2.75"	98.11
☐	FZSDT6036C	60.1"	62.6"	36.5"	39"	2.75"	102.29
☐	FZSDT6040C	60.1"	62.6"	40.5"	43"	2.75"	108.03
☐	FZSDT6042C	60.1"	62.6"	42.5"	45"	2.75"	108.47
☐	FZSDT6048C	60.1"	62.6"	48.5"	51"	2.75"	117.95
☐	FZSDT6332C	64"	66.5"	32.5"	35"	2.75"	100.31
☐	FZSDT6336C	64"	66.5"	36.5"	39"	2.75"	102.52
☐	FZSDT6340C	64"	66.5"	40.5"	43"	2.75"	110.23
☐	FZSDT6642C	65.9"	68.4"	42.5"	45"	2.75"	115.96
☐	FZSDT6648C	65.9"	68.4"	48.5"	51"	2.75"	122.36
☐	FZSDT6736C	68"	70.5"	36.5"	39"	2.75"	104.72
☐	FZSDT7236C	71.9"	74.4"	36.5"	39"	2.75"	108.03
☐	FZSDT7242C	71.9"	74.4"	42.5"	45"	2.75"	120.59
☐	FZSDT7248C	71.9"	74.4"	48.5"	51"	2.75"	128.97
☐	FZSDT7940C	79.7"	82.2"	40.5"	43"	2.75"	127.87

To Be Specified: Color

☐ 31 White		White 31		Dk Grey 40
☐ 32 Cameo		Cameo 32		Black 09
☐ 40 Dark Grey				
☐ 09 Black				

Meets or Exceeds the Following Specification

- ASME A112.18.1 / CSA B125.125.1-11
- cUPC® • IAPMO

