

Features

- Heavy Duty SMC Sheet Molding Compound Material
- Trimslate shower bases with our unique adjustable depth threshold.
- Maximum depth and width can be adjusted by up to 2-1/2" without any trimming of the base.
- Trimslate bases can also be customized in the field to fit your space. Trim up to 4" in width from either side or up to 2" in depth away from drain.
- Each base is supplied with two 80" long add on trimmable thresholds with a 45-degree mitered edge.
- The threshold has a 4" wide flat surface to accommodate shower doors.
- Modern stainless steel drain cover conceals a conventional 2" shower drain (not supplied). Color-matched SMC cover for SMFZSDT5140C, SMFZSDT6040C, SMFZSDT6340C, and SMFZSDT7940C.
- The slate floor has a lightly textured and slip-resistant surface that makes it safe, yet remains easy to clean.
- 1" high aluminum tiling flange included
- Weight capacity of 2204.6 pounds (1000 kg).
- 10 Year Limited Residential / 3 Year Commercial Warranty



Stock Sized Specified Models

	Model No.	Min Length A	Max Length A	Min Length B	Max Length B	Height	Ship Wt. (lbs)
☐	SMFZSDT4836C	48.2"	50.7"	36.5"	39"	2.75"	94.80
☐	SMFZSDT5140C	52.2"	54.7"	40.5"	43"	2.75"	102.74
☐	SMFZSDT6032C	60.1"	62.6"	32.5"	35"	2.75"	98.11
☐	SMFZSDT6036C	60.1"	62.6"	36.5"	39"	2.75"	102.29
☐	SMFZSDT6040C	60.1"	62.6"	40.5"	43"	2.75"	108.03
☐	SMFZSDT6042C	60.1"	62.6"	42.5"	45"	2.75"	108.47
☐	SMFZSDT6048C	60.1"	62.6"	48.5"	51"	2.75"	117.95
☐	SMFZSDT6332C	64"	66.5"	32.5"	35"	2.75"	100.31
☐	SMFZSDT6336C	64"	66.5"	36.5"	39"	2.75"	102.52
☐	SMFZSDT6340C	64"	66.5"	40.5"	43"	2.75"	110.23
☐	SMFZSDT6642C	65.9"	68.4"	42.5"	45"	2.75"	115.96
☐	SMFZSDT6648C	65.9"	68.4"	48.5"	51"	2.75"	122.36
☐	SMFZSDT6736C	68"	70.5"	36.5"	39"	2.75"	104.72
☐	SMFZSDT7236C	71.9"	74.4"	36.5"	39"	2.75"	108.03
☐	SMFZSDT7242C	71.9"	74.4"	42.5"	45"	2.75"	120.59
☐	SMFZSDT7248C	71.9"	74.4"	48.5"	51"	2.75"	128.97
☐	SMFZSDT7940C	79.7"	82.2"	40.5"	43"	2.75"	127.87

To Be Specified: Color

☐ 31 White		
☐ 32 Cameo	White 31	Dk Grey 40
☐ 40 Dark Grey		
☐ 09 Black	Cameo 32	Black 09

Meets or Exceeds the Following Specification

- ASME A112.18.1 / CSA B125.125.1-11
- cUPC® • IAPMO 

