

FEATURES

- ALL-IN-ONE Kit includes close coupled 2-pc. HET toilet. Combination elongated front bowl and tank with seat. Wax seal, hold-down bolts.
- 12" (305mm) rough-in.
- Vitreous china.
- High efficiency (1.28 gpf/4.8 Lpf).
- Gravity feed, siphon action bowl.
- 2" fully-glazed trapway.
- 3" flush valve.
- 16-1/2" comfort height.
- Chrome trip lever.
- 2 color-matched bolt caps.
- 5 Year Limited Residential Warranty / 1 Year Commercial Warranty
- Meets strict flushing performance criterion established by the EPA (environmental protection Agency) WaterSense program
- High efficiency toilets use at least 20% less water than standard 1.6 GPF toilets
- This product can help a building earn Water Efficiency points in the LEED Green Building Rating System™

COLORS

- White

OPTIONS

- Tank with right-hand trip lever.

Specified Model

| MODEL NO. | DESCRIPTION | Length | Width | Height |
|-----------------------------|----------------------------|--------|---------|----------|
| COMPLETE TOILET KITS | | | | |
| SMBTS1-1555 | Elongated Front Toilet Kit | 30" | 18 1/8" | 31 1/10" |

Specified Model

01- White

Compliance Certifications - Meets or Exceeds the Following Specifications


- ASME A112.19.2M-2008/CSA B45.1-2008
- UPC®, National Plumbing Code of Canada, IPC & IRC
- EPA Water Sense Tank-Type High Efficient Toilet Specs



Meets the Americans with Disabilities Act guidelines and ANSI A117.1 requirements for accessible and usable building facilities-check local codes



TOILETS/LAVS



This toilet is designed to rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply not included with fixture and must be ordered separately. Dimension shown for location of supply is suggested. For additional information refer to installation instructions supplied.